

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NPA-25 SERIES" TP, MF SUBMERSIBLE PUMP SETS FOR 7" (175 MM)
BOREWELLS SUITABLE FOR 415 V (-15 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 100 MM	DISCHARGE IN LPM						
					0	650	825	975	1050	1150	1350
NP25V7/3SU	7.5	5.5	3	HEAD IN MTRS	48	36	33	30	27	24	18
NP25V7/3	7.5	5.5	3		48	36	33	30	27	24	18
NP25V7/4SU	10.0	7.5	4		64	48	44	40	36	32	24
NP25V7/4	10.0	7.5	4		64	48	44	40	36	32	24
NP25V7/5	12.5	9.3	5		80	60	55	50	45	40	30
NP25V7/6	15.0	11.0	6		96	72	66	60	54	48	36
NP25V7/7	17.5	13.0	7		112	84	77	70	63	56	42
NP25V7/8	20.0	15.0	8		128	96	88	80	72	64	48

NORIA "NPA-30 SERIES" TP, MF SUBMERSIBLE PUMP SETS FOR 7" (175 MM)
BOREWELLS SUITABLE FOR 415 V (-15 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 100 MM	DISCHARGE IN LPM						
					0	450	925	1080	1250	1325	1520
NP30V7/3SU	10.0	7.5	3	HEAD IN MTRS	48	36	33	30	27	24	18
NP30V7/3	10.0	7.5	3		48	36	33	30	27	24	18
NP30V7/4	12.5	9.3	4		64	48	44	40	36	32	24
NP30V7/5	15.0	11.0	5		80	60	55	50	45	40	30
NP30V7/6	17.5	13.0	6		96	72	66	60	54	48	36
NP30V7/7	20.0	15.0	7		112	84	77	70	63	56	42

NORIA "NPA-40 SERIES" TP, MF SUBMERSIBLE PUMP SETS FOR 7" (175 MM)
BOREWELLS SUITABLE FOR 415 V (-15 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 100 MM	DISCHARGE IN LPM						
					0	600	840	1120	1400	1650	2050
NP40V7/2SU	7.5	5.5	2	HEAD IN MTRS	36	28	24	22	20	18	14
NP40V7/2	7.5	5.5	2		36	28	24	22	20	18	14
NP40V7/3	12.5	9.3	3		54	42	36	33	30	27	21
NP40V7/4	15.0	11.0	4		72	56	48	44	40	36	28
NP40V7/5	20.0	15.0	5		90	70	60	55	50	45	35
NP40V7/6	25.0	18.5	6		108	84	72	66	60	54	42

V7

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NPA-50 SERIES" TP, MF SUBMERSIBLE PUMP SETS FOR 7" (175 MM)
BOREWELLS SUITABLE FOR 415 V (-15 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 100 MM	DISCHARGE IN LPM						
					0	750	1150	1350	1500	1750	2200
NP50V7/2SU	10.0	7.5	2	HEAD IN MTRS	38	32	28	26	24	22	18
NP50V7/2	10.0	7.5	2		38	32	28	26	24	22	18
NP50V7/3	15.0	11.0	3		57	48	42	39	36	33	27
NP50V7/4	20.0	15.0	4		76	64	56	52	48	44	36
NP50V7/5	25.0	18.5	5		95	80	70	65	60	55	45

NORIA "NPA- 60 SERIES" TP, MF SUBMERSIBLE PUMP SETS FOR 7" (175 MM)
BOREWELLS SUITABLE FOR 415 V (-15 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 100 MM	DISCHARGE IN LPM						
					0	850	1050	1450	1550	1850	2250
NP60V7/1	6.0	4.5	1	HEAD IN MTRS	21	18	16	14	12	10	8
NP60V7/2	12.5	9.3	2		42	36	32	28	24	20	16
NP60V7/3	20.0	15.0	3		63	54	48	42	36	30	24
NP60V7/4	25.0	18.5	4		84	72	64	56	48	40	32

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP-261 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	100	290	370	420	460	520	640
NP261MF/3	3.0	2.2	3	HEAD IN MTRS	33	30	27	25	23	20	17	13
NP261MF/4	4.0	3.0	4		44	40	36	33	30	26	23	17
NP261MF/5	5.0	3.7	5		55	50	45	41	38	33	28	21
NP261MF/6	6.0	4.5	6		66	60	54	50	45	40	34	26
NP261MF/8	7.5	5.5	8		88	80	73	66	60	53	45	34
NP261MF/10	10.0	7.5	10		110	100	91	83	75	66	57	43
NP261MF/12	12.5	9.3	12		132	120	109	99	90	79	68	54
NP261MF/14	15.0	11.0	15		154	140	136	124	112	98	82	64
NP261MF/18	17.5	13.0	18		198	180	163	148	135	117	99	77
NP261MF/20	20.0	15.0	20		220	200	181	165	150	130	110	85
NP261MF/25	25.0	18.5	25		275	250	225	200	175	150	125	105

NORIA "NP-262 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	100	350	400	500	550	620	750
NP262MF/5	5.0	3.7	4	HEAD IN MTRS	48	44	36	33	30	26	23	17
NP262MF/6	6.0	4.5	5		60	55	45	41	38	33	28	21
NP262MF/8	7.5	5.5	6		72	66	54	50	45	40	34	26
NP262MF/10	10.0	7.5	8		96	88	73	66	60	53	45	34
NP262MF/12	12.5	9.3	10		120	110	91	83	75	66	57	43
NP262MF/14	15.0	11.0	12		144	132	109	99	90	79	68	51
NP262MF/18	17.5	13.0	14		168	154	128	116	106	96	80	60
NP262MF/20	20.0	15.0	18		216	198	146	132	128	120	90	68
NP262MF/25	25.0	18.5	20		240	220	182	168	150	130	114	86

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP-271 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	220	500	600	660	700	750	800
NP271MF/2	3.0	2.2	2	HEAD IN MTRS	24	22	18	17	15	14	13	11
NP271MF/3	5.0	3.7	3		36	34	27	25	23	22	20	17
NP271MF/4	6.0	4.5	4		48	44	36	33	30	28	26	23
NP271MF/5	7.5	5.5	5		60	55	45	41	38	35	33	28
NP271MF/6	10.0	7.5	6		72	66	54	50	45	43	40	34
NP271MF/8	12.5	9.3	8		96	88	73	66	60	56	53	45
NP271MF/10	15.0	11.0	10		120	110	91	83	75	60	66	57
NP271MF/11	17.5	13.0	11		132	121	100	91	83	86	72	62
NP271MF/12	20.0	15.0	12		144	132	110	99	90	85	79	68
NP271MF/16	25.0	18.5	16		176	170	150	130	120	115	105	95

NORIA "NP-302 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 80 MM	DISCHARGE IN LPM							
					0	300	650	750	800	875	975	1080
NP302MF/2	4.0	3.0	2	HEAD IN MTRS	22	20	18	17	15	13	11	10
NP302MF/3	6.0	4.5	3		33	30	27	25	23	20	17	14
NP302MF/4	7.5	5.5	4		44	40	36	33	30	26	23	18
NP302MF/5	10.0	7.5	5		55	50	45	41	38	33	28	22
NP302MF/6	12.5	9.3	6		66	60	54	50	45	40	34	28
NP302MF/8	15.0	11.0	8		88	80	73	66	60	53	45	36
NP302MF/10	20.0	15.0	10		110	100	91	83	75	66	57	45
NP302MF/12	25.0	18.5	12		132	120	109	99	90	79	68	54

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP-323 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6" (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 80 MM	DISCHARGE IN LPM							
					0	400	800	900	1000	1200	1250	1360
NP323MF/2	5.0	3.7	2	HEAD IN MTRS	22	20	17	16	14	13	12	10
NP323MF/3	7.5	5.5	3		33	30	26	23	22	19	17	15
NP323MF/4	10.0	7.5	4		44	40	35	31	29	25	22	20
NP323MF/5	12.5	9.3	5		55	50	43	39	36	32	28	25
NP323MF/6	15.0	11.0	6		66	60	52	47	43	38	33	30
NP323MF/8	20.0	15.0	8		88	80	70	62	58	50	43	40
NP323MF/10	25.0	18.5	10		110	100	86	78	72	64	55	50

NORIA "NP-333 SERIES" TP, SAND PROOF MIXED FLOW SUBMERSIBLE PUMP SETS FOR 6" (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 80 MM	DISCHARGE IN LPM							
					0	500	900	1000	1100	1300	1350	1450
NP333MF/2	6.0	4.5	2	HEAD IN MTRS	23	22	19	18	16	14	13	11
NP333MF/3	10.0	7.5	3		33	32	29	26	24	21	19	16
NP333MF/4	12.5	9.3	4		45	43	39	35	32	28	25	20
NP333MF/5	15.0	11.0	5		55	52	48	44	40	35	31	25
NP333MF/6	17.5	13.0	6		67	63	58	53	48	42	37	29
NP333MF/7	20.0	15.0	7		78	72	68	62	56	49	43	35
NP333MF/9	25.0	18.5	9		100	96	87	79	72	63	55	44

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP- 03 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	45	85	105	130	175	210
NP03RF/10	3.0	2.2	10	HEAD IN MTRS	110	100	90	80	70	60	50
NP03RF/12	4.0	3.0	12		132	120	108	96	84	72	60
NP03RF/15	5.0	3.7	15		165	150	135	120	105	90	75
NP03RF/18	6.0	4.5	18		198	180	162	144	126	108	90
NP03RF/24	7.5	5.5	24		264	240	216	192	168	144	120
NP03RF/30	10.0	7.5	30		330	300	270	240	210	180	150
NP03RF/35	12.5	9.3	35		385	350	315	280	245	210	175

NORIA "NP- 04 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	65	115	160	180	215	230
NP04RF/8	3.0	2.2	8	HEAD IN MTRS	88	80	72	64	56	48	40
NP04RF/10	4.0	3.0	10		110	100	90	80	70	60	50
NP04RF/12	5.0	3.7	12		132	120	108	96	84	72	60
NP04RF/15	6.0	4.5	15		165	150	135	120	105	90	75
NP04RF/18	7.5	5.5	18		198	180	162	144	126	108	90
NP04RF/25	10.0	7.5	25		275	250	225	200	175	150	125
NP04RF/30	12.5	9.3	30		330	300	270	240	210	180	150
NP04RF/34	15.0	34.0	34		374	340	306	272	238	204	170

NORIA "NP- 05 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	90	160	190	230	260	280
NP05RF/6	3.0	2.2	6	HEAD IN MTRS	72	60	54	48	42	36	30
NP05RF/8	4.0	3.0	8		96	80	72	64	56	48	40
NP05RF/10	5.0	3.7	10		120	100	90	80	70	60	50
NP05RF/12	6.0	4.5	12		144	120	108	96	84	72	60
NP05RF/15	7.5	5.5	15		180	150	135	120	105	90	75
NP05RF/18	10.0	7.5	18		216	180	162	144	126	108	90
NP05RF/24	12.5	9.3	24		288	240	216	192	168	144	120
NP05RF/30	15.0	11.0	30		360	300	270	240	210	180	150
NP05RF/35	17.5	13.0	35		420	350	315	280	245	210	175
NP05RF/40	20.0	15.0	40		480	400	360	320	280	240	200

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP- 06 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	170	200	220	260	280	310
NP06RF/5	3.0	2.2	5	HEAD IN MTRS	60	50	45	40	35	30	25
NP06RF/8	5.0	3.7	8		96	80	72	64	56	48	40
NP06RF/10	6.0	4.5	10		120	100	90	80	70	60	50
NP06RF/12	7.5	5.5	12		144	120	108	96	84	72	60
NP06RF/15	10.0	7.5	15		180	150	135	120	105	90	75
NP06RF/20	12.5	9.3	20		240	200	180	160	140	120	100
NP06RF/24	15.0	11.2	24		288	240	216	192	168	144	120
NP06RF/26	17.5	13.1	26		312	260	234	208	182	156	130
NP06RF/32	20.0	14.7	32		384	320	288	256	224	192	160

NORIA "NP- 08 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	180	270	290	340	370	400
NP08RF/4	3.0	2.2	4	HEAD IN MTRS	48	40	36	32	28	24	20
NP08RF/6	5.0	3.7	6		72	60	54	48	42	36	30
NP08RF/7	6.0	4.5	8		96	80	72	64	56	48	40
NP08RF/10	7.5	5.5	10		120	100	90	80	70	60	50
NP08RF/12	10.0	7.5	12		144	120	108	96	84	72	60
NP08RF/14	12.5	9.3	14		168	140	126	112	98	84	70
NP08RF/18	15.0	11.2	18		216	180	162	144	126	108	90
NP08RF/20	17.5	13.1	20		240	200	180	160	140	120	100
NP08RF/22	20.0	14.9	22		264	220	198	176	154	132	110
NP08RF/30	25.0	18.7	30		360	300	270	240	210	180	150

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP- 10 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	250	310	350	400	415	450
NP10RF/3	3.0	2.2	3	HEAD IN MTRS	36	30	27	24	21	18	15
NP10RF/4	4.0	3.0	4		48	40	36	32	28	24	20
NP10RF/5	5.0	3.7	5		60	50	45	40	35	30	25
NP10RF/6	6.0	4.5	6		72	60	54	48	42	36	30
NP10RF/8	7.5	5.5	8		96	80	72	64	56	48	40
NP10RF/10	10.0	7.5	10		120	100	90	80	70	60	50
NP10RF/12	12.5	9.3	12		144	120	108	96	84	72	60
NP10RF/15	15.0	11.2	15		180	150	135	120	105	90	75
NP10RF/18	17.5	13.1	18		216	180	162	144	126	108	90
NP10RF/20	20.0	14.9	20		240	200	180	160	140	120	100

NORIA "NP- 12 SERIES" TP, SAND PROOF REDIAL FLOW SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM						
					0	280	350	460	500	540	600
NP12RF/3	4.0	3.0	3	HEAD IN MTRS	36	30	27	24	21	18	15
NP12RF/4	5.0	3.7	4		48	40	36	32	28	24	20
NP12RF/5	6.0	4.5	5		60	50	45	40	35	30	25
NP12RF/6	7.5	5.6	6		72	60	54	48	42	36	30
NP12RF/8	10.0	7.4	8		96	80	72	64	56	48	40
NP12RF/10	12.5	9.3	10		120	100	90	80	70	60	50
NP12RF/12	15.0	11.2	12		144	120	108	96	84	72	60
NP12RF/14	17.5	13.1	14		168	140	126	112	98	84	70
NP12RF/16	20.0	14.9	16		192	160	144	128	112	96	80
NP12RF/20	25.0	18.7	20		240	200	180	160	140	120	100

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NPA-04 SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM								
					0	40	60	70	110	140	165	180	190
NP04V5/7	3	2.2	7	HEAD IN MTRS	78	72	64	64	56	45	40	35	28
NP04V5/8	3	2.2	8		88	80	75	72	64	56	48	45	40
NP04V5/10	4	3.0	10		110	100	95	90	80	70	60	55	50
NP04V5/12	5	3.7	12		132	120	115	108	96	84	70	65	60
NP04V5/15	6	4.5	15		165	150	140	135	120	105	90	85	75
NP04V5/18	7.5	5.5	18		198	180	172	162	144	126	108	95	90
NP04V5/20	7.5	5.5	20		220	200	190	180	160	140	120	110	100

NORIA "NPA-05 SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM								
					0	70	90	115	135	170	200	220	230
NP05V5/6	3	2.2	6	HEAD IN MTRS	66	60	55	50	45	40	36	30	25
NP05V5/8	4	3.0	8		88	80	75	70	65	55	48	40	30
NP05V5/10	5	3.7	10		110	100	95	90	80	70	60	50	40
NP05V5/12	6	4.5	12		132	120	115	110	95	85	72	60	50
NP05V5/14	7.5	5.5	14		154	140	130	125	110	95	84	70	60
NP05V5/15	7.5	5.5	15		165	150	140	135	120	105	90	75	65
NP05V5/20	10.0	7.5	20		220	200	190	180	160	140	120	100	90

NORIA "NPA-06 SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM								
					0	100	120	135	150	190	225	250	270
NP06V5/5	3	2.2	5	HEAD IN MTRS	55	50	47	45	42	40	35	30	25
NP06V5/7	4	3.0	7		77	70	66	63	56	52	49	42	35
NP06V5/8	5	3.7	8		88	80	75	72	67	64	56	48	40
NP06V5/10	6	4.5	10		110	100	95	90	84	80	70	60	50
NP06V5/12	7.5	5.5	12		132	120	114	108	102	96	84	72	60
NP06V5/16	10.0	7.5	16		176	160	152	144	134	128	112	96	80

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NPA-08 SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM								
					0	120	160	170	190	210	250	280	300
NP08V5/4	3	2.2	4	HEAD IN MTRS	44	38	36	34	33	32	21	18	12
NP08V5/5	4	3.0	5		55	48	45	43	42	40	26	20	15
NP08V5/6	5	3.7	6		66	57	54	52	50	48	32	24	18
NP08V5/8	6	4.5	8		88	78	72	69	66	64	42	32	24
NP08V5/10	7.5	5.5	10		110	95	90	88	83	80	53	40	30
NP08V5/12	10.0	7.5	12		132	114	104	103	100	96	63	48	38

NORIA "NPA-10 SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM								
					0	160	200	240	280	320	340	360	400
NP10V5/3	3	2.2	3	HEAD IN MTRS	33	29	27	26	24	20	16	12	9
NP10V5/4	4	3.0	4		44	40	38	34	32	26	21	18	12
NP10V5/5	5	3.7	5		55	48	45	43	40	33	28	20	16
NP10V5/6	6	4.5	6		66	57	54	52	48	39	32	24	18
NP10V5/8	7.5	5.5	8		88	78	72	69	64	52	42	32	24
NP10V5/10	10.0	7.5	10		110	95	90	86	80	65	53	40	30

NORIA "NPA-10M SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM								
					0	150	230	280	360	400	450	470	520
NP10V5M/3	3	2.2	3	HEAD IN MTRS	30	28	25	24	21	20	18	17	15
NP10V5M/4	4	3.0	4		40	35	33	32	28	26	24	23	19
NP10V5M/5	5	3.7	5		50	44	42	40	35	33	30	29	25
NP10V5M/6	6	4.5	6		60	52	50	48	42	39	36	34	30
NP10V5M/8	7.5	5.5	8		80	70	68	64	58	52	48	45	40
NP10V5M/10	10.0	7.5	10		100	88	83	80	70	65	60	55	50

BOREWELL SUBMERSIBLE PUMPSETS



NORIA "NPA-12M SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 5" (125 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM								
					0	200	300	370	450	520	560	600	650
NP12V5M/3	4	3.0	3	HEAD IN MTRS	30	27	25	24	21	20	18	17	15
NP12V5M/4	5	3.7	4		40	26	34	32	28	26	24	22	20
NP12V5M/5	6	4.5	5		50	44	42	40	35	33	30	28	25
NP12V5M/6	7.5	5.5	6		60	54	50	48	42	39	38	33	30
NP12V5M/8	10.0	7.5	8		80	72	66	64	58	52	48	44	40

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP- 03 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	45	85	105	130	175	210
NP03RF/10	3.0	2.2	10	HEAD IN MTRS	110	100	90	80	70	60	50
NP03RF/12	4.0	3.0	12		132	120	108	96	84	72	60
NP03RF/15	5.0	3.7	15		165	150	135	120	105	90	75
NP03RF/18	6.0	4.5	18		198	180	162	144	126	108	90
NP03RF/24	7.5	5.5	24		264	240	216	192	168	144	120

NORIA "NP- 04 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	65	115	160	180	215	230
NP04RF/8	3.0	2.2	8	HEAD IN MTRS	88	80	72	64	56	48	40
NP04RF/10	4.0	3.0	10		110	100	90	80	70	60	50
NP04RF/12	5.0	3.7	12		132	120	108	96	84	72	60
NP04RF/15	6.0	4.5	15		165	150	135	120	105	90	75
NP04RF/18	7.5	5.5	18		198	180	162	144	126	108	90

NORIA "NP- 05 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	90	160	190	230	260	280
NP05RF/6	3.0	2.2	6	HEAD IN MTRS	72	60	54	48	42	36	30
NP05RF/8	4.0	3.0	8		96	80	72	64	56	48	40
NP05RF/10	5.0	3.7	10		120	100	90	80	70	60	50
NP05RF/12	6.0	4.5	12		144	120	108	96	84	72	60
NP05RF/15	7.5	5.5	15		180	150	135	120	105	90	75

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP- 06 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	170	200	220	260	280	310
NP06RF/5	3.0	2.2	5	HEAD IN MTRS	60	50	45	40	35	30	25
NP06RF/8	5.0	3.7	8		96	80	72	64	56	48	40
NP06RF/10	6.0	4.5	10		120	100	90	80	70	60	50
NP06RF/12	7.5	5.5	12		144	120	108	96	84	72	60

NORIA "NP- 08 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	180	270	290	340	370	400
NP08RF/4	3.0	2.2	4	HEAD IN MTRS	48	40	36	32	28	24	20
NP08RF/6	5.0	3.7	6		72	60	54	48	42	36	30
NP08RF/7	6.0	4.5	8		96	80	72	64	56	48	40
NP08RF/10	7.5	5.5	10		120	100	90	80	70	60	50

NORIA "NP- 10 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50MM	DISCHARGE IN LPM						
					0	250	310	350	400	415	450
NP10RF/3	3.0	2.2	3	HEAD IN MTRS	36	30	27	24	21	18	15
NP10RF/5	5.0	3.7	5		60	50	45	40	35	30	25
NP10RF/6	6.0	4.5	6		72	60	54	48	42	36	30
NP10RF/8	7.5	5.5	8		96	80	72	64	56	48	40

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP-261 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	100	290	370	420	460	520	640
NP261V6/3	3	2.2	3	HEAD IN MTRS	33	30	27	25	23	20	17	13
NP261V6/4	4	3	4		44	40	36	33	30	26	23	17
NP261V6/5	5	3.7	5		55	50	45	41	38	33	28	21
NP261V6/6	6	4.5	6		66	60	54	50	45	40	34	26
NP261V6/8	7.5	5.5	8		88	80	73	66	60	53	45	34

NORIA "NP-262 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	100	350	400	500	550	620	750
NP262V6/5	5	3.7	4	HEAD IN MTRS	48	44	36	33	30	26	23	17
NP262V6/6	6	4.5	5		60	55	45	41	38	33	28	21
NP262V6/8	7.5	5.5	6		72	66	54	50	45	40	34	26

NORIA "NP-271 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM							
					0	220	500	600	660	700	750	800
NP271V6/2	3	2.2	2	HEAD IN MTRS	24	22	18	17	15	14	13	11
NP271V6/3	5	3.7	3		36	34	27	25	23	22	20	17
NP271V6/4	6	4.5	4		48	44	36	33	30	28	26	23
NP271V6/5	7.5	5.5	5		60	55	45	41	38	35	33	28

NORIA "NP-302 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 80 MM	DISCHARGE IN LPM							
					0	300	650	750	800	875	975	1080
NP302V6/3	6	4.5	3	HEAD IN MTRS	33	30	27	25	23	20	17	14
NP302V6/4	7.5	5.5	4		44	40	36	33	30	26	23	18

NORIA "NP-323 (SU) SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 80 MM	DISCHARGE IN LPM							
					0	400	800	900	1000	1200	1250	1360
NP323V6/2	5	3.7	2	HEAD IN MTRS	22	20	17	16	14	13	12	10
NP323V6/3	7.5	5.5	3		33	30	26	23	22	19	17	15

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "50 FEET SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6" (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					70	90	135	150	165	200	220
NPH6S/5	3.0	2.2	5	HEAD IN MTRS	75	70	65	60	55	40	30
NPH6S/8	5.0	3.7	8		120	112	106	96	80	60	45
NPH6S/10	6.0	4.5	10		150	142	130	120	100	80	55
NPH6S/12	7.5	5.5	12		180	170	160	140	125	95	70
NPH6S/15	10.0	7.5	16		240	230	210	190	160	130	85
NPH6S/20	12.5	9.3	20		300	280	260	240	200	160	120
NPH6S/24	15.0	11.2	24		370	350	330	290	250	190	140
NPH6S/26	17.5	13.1	30		450	420	400	360	300	230	170

NORIA "50 FEET SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6" (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	130	160	180	220	250	290
NPH8S/4	3.0	2.2	4	HEAD IN MTRS	64	58	52	48	40	32	26
NPH8S/6	5.0	3.7	6		96	87	78	72	60	49	39
NPH8S/8	6.0	4.5	8		128	115	105	95	80	65	50
NPH8S/10	7.5	5.5	10		160	145	130	120	100	80	65
NPH8S/12	10.0	7.5	12		192	174	156	144	120	100	80
NPH8S/14	12.5	9.3	14		240	215	195	180	150	120	100
NPH8S/18	15.0	11.2	18		290	260	235	215	180	145	120
NPH8S/20	17.5	13.1	20		350	200	180	160	140	120	100
NPH8S/22	20.0	14.9	25		400	360	325	300	250	200	170

V6HH TABLES

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "50 FEET SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 50 MM	DISCHARGE IN LPM						
					0	185	230	260	295	330	360
NPH10S/3	3.0	2.2	3	HEAD IN MTRS	49	44	40	36	30	26	20
NPH10S/4	4.0	3.0	4		65	58	53	48	40	34	27
NPH10S/5	5.0	3.7	5		82	73	66	60	50	43	34
NPH10S/6	6.0	4.5	6		98	87	79	72	60	51	41
NPH10S/8	7.5	5.5	8		130	116	106	96	80	68	54
NPH10S/10	10.0	7.5	10		163	145	132	120	100	85	68
NPH10S/12	12.5	9.3	12		196	174	158	144	120	102	82
NPH10S/15	15.0	11.2	15		245	218	198	180	150	128	102
NPH10S/18	17.5	13.1	18		293	261	238	216	180	153	122
NPH10S/20	20.0	14.9	20		326	290	264	240	200	170	136

NORIA "50 FEET SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM						
					0	220	275	340	390	440	495
NPH12S/3	4.0	3.0	3	HEAD IN MTRS	47	44	39	36	29	26	20
NPH12S/4	5.0	3.7	4		63	59	52	48	39	34	27
NPH12S/5	6.0	4.5	5		79	74	65	60	49	43	34
NPH12S/6	7.5	5.6	6		95	88	78	72	59	51	41
NPH12S/8	10.0	7.4	8		126	118	104	96	76	68	54
NPH12S/10	12.5	9.3	10		158	147	130	120	98	85	68
NPH12S/12	15.0	11.0	12		190	176	156	144	118	102	82
NPH12S/14	17.5	13.0	14		221	206	182	168	137	119	95

V6HH TABLES

BOREWELL SUBMERSIBLE PUMPSETS



NORIA "50 FEET SERIES" TP, SAND PROOF SUBMERSIBLE PUMP SETS FOR 6 " (150 MM)
BOREWELLS SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	KW	STAGE	DELIVERY SIZE 65 MM	DISCHARGE IN LPM						
					0	255	375	425	475	525	605
NPH15S/3	5.0	3.7	3	HEAD IN MTRS	47	44	39	36	29	26	20
NPH15S/4	6.0	4.5	4		63	59	52	48	39	34	27
NPH15S/5	7.5	5.6	5		79	74	65	60	49	43	34
NPH15S/6	10.0	7.5	6		95	88	78	72	59	51	41
NPH15S/8	12.5	9.3	8		126	118	104	96	76	68	54
NPH15S/10	15.0	11.0	10		158	147	130	120	98	85	68
NPH15S/12	17.5	13.0	12		190	176	156	144	118	102	82
NPH15S/14	20.0	15.0	14		221	206	182	168	137	119	95
NPH15S/16	25.0	18.5	16		253	235	208	192	157	136	109

V6HH TABLES

BOREWELL SUBMERSIBLE PUMPSETS

"NORIA" BRAND V-3 SUBMERSIBLE PUMPSET SP SAND PROOF SUITABLE FOR 80MM (3")
 BOREWELL IN 240 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY
 V 3-SUBMERSIBLE PUMP OD 70 MM

MODEL	HP	STAGE	DELIVERY	HEAD IN MTRS	DISCHARGE IN LPM								
					30	35	40	45	50	55	60	65	70
NP3R4L	0.50	9	1.25"		25	23	21	19	17	15	10	6	2
NP3R4L	0.75	12	1.25"		34	31	28	25	23	20	14	7	4
NP3R4L	1.00	16	1.25"		45	41	38	34	30	26	19	9	6
NP3R4L	1.25	20	1.25"		56	52	47	42	38	33	24	12	8
NP3R4L	1.50	25	1.25"		71	65	59	53	47	41	29	15	10

"NORIA" BRAND V-3 SUBMERSIBLE PUMPSET SP SAND PROOF SUITABLE FOR 80MM (3")
 BOREWELL IN 240 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY
 V 3-SUBMERSIBLE PUMP OD 70 MM

MODEL	HP	STAGE	DELIVERY	HEAD IN MTRS	DISCHARGE IN LPM								
					30	35	40	45	50	55	60	65	70
NP3R5L	0.50	6	1.25"		18	16	14	13	12	11	10	8	4
NP3R5L	0.75	9	1.25"		27	24	22	20	18	16	15	11	6
NP3R5L	1.00	12	1.25"		36	32	29	26	24	22	20	15	8
NP3R5L	1.25	15	1.25"		45	40	36	33	30	27	25	19	10
NP3R5L	1.50	18	1.25"		54	48	43	39	36	33	30	22	12

V3 TABLES

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP - NANO10 SERIES" TP, SAND PROOF SUB. PUMP SETS FOR 6 " (150 MM) BOREWELLS
SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	STAGE	HEAD IN MTRS	DISCHARGE IN LPM						
				0	210	290	380	460	600	780
NPNN10/3	3.0	3	HEAD IN MTRS	39	33	28	25	18	15	9
NPNN10/4	4.0	4		52	44	37	34	24	20	12
NPNN10/5	5.0	5		65	55	47	43	30	25	15
NPNN10/6	6.0	6		78	66	56	51	36	30	18
NPNN10/8	7.5	8		104	88	75	68	48	40	24
NPNN10/10	10.0	10		130	110	93	85	60	50	30
NPNN10/12	12.5	12		156	132	112	102	72	60	36
NPNN10/15	15.0	15		195	165	140	127	90	75	45
NPNN10/18	17.5	18		234	198	168	153	108	90	54
NPNN10/20	20.0	20		260	220	187	170	120	100	60

NORIA "NP - NANO12 SERIES" TP, SAND PROOF SUB. PUMP SETS FOR 6 " (150 MM) BOREWELLS
SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	STAGE	HEAD IN MTRS	DISCHARGE IN LPM						
				0	270	350	480	540	680	860
NPNN12/2	3.0	2	HEAD IN MTRS	26	22	28	17	12	10	6
NPNN12/3	4.0	3		39	33	37	25	18	15	9
NPNN12/4	5.0	4		52	44	47	43	24	20	12
NPNN12/5	6.0	5		65	55	56	43	30	25	15
NPNN12/6	7.5	6		78	66	75	51	36	30	18
NPNN12/8	10.0	8		104	88	93	68	48	40	24
NPNN12/10	12.5	10		130	110	112	85	60	50	30
NPNN12/12	15.0	12		156	132	140	127	72	60	36
NPNN12/14	17.5	14		182	154	168	119	84	70	42
NPNN12/16	20.0	16		208	176	187	136	96	80	48

NANO T TYPE TABLES

BOREWELL SUBMERSIBLE PUMPSETS

NORIA "NP - NANO15 SERIES" TP, SAND PROOF SUB. PUMP SETS FOR 6 " (150 MM) BOREWELLS
SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	STAGE	HEAD IN MTRS	DISCHARGE IN LPM						
				0	350	430	560	680	840	980
NPNN15/2	3.0	2	HEAD IN MTRS	26	22	28	17	12	10	6
NPNN15/3	5.0	3		39	33	37	25	18	15	9
NPNN15/4	6.0	4		52	44	47	43	24	20	12
NPNN15/5	7.5	5		65	55	56	43	30	25	15
NPNN15/6	10.0	6		78	66	75	51	36	30	18
NPNN15/8	12.5	8		104	88	93	68	48	40	24
NPNN15/10	15.0	10		130	110	112	85	60	50	30
NPNN15/12	17.5	12		156	132	140	127	72	60	36
NPNN15/14	20.0	14		182	154	168	119	84	70	42

NORIA "NP - NANO20 SERIES" TP, SAND PROOF SUB. PUMP SETS FOR 6 " (150 MM) BOREWELLS
SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	STAGE	HEAD IN MTRS	DISCHARGE IN LPM						
				0	425	610	780	920	1040	1180
NPNN20/2	4.0	2	HEAD IN MTRS	26	22	28	17	12	10	6
NPNN20/3	6.0	3		39	33	37	25	18	15	9
NPNN20/4	7.5	4		52	44	47	43	24	20	12
NPNN20/5	10.0	5		65	55	56	43	30	25	15
NPNN20/6	12.5	6		78	66	75	51	36	30	18
NPNN20/8	15.0	8		104	88	93	68	48	40	24
NPNN20/10	17.5	10		130	110	112	85	60	50	30
NPNN20/12	20.0	12		156	132	140	127	72	60	36

NORIA "NP - NANO25 SERIES" TP, SAND PROOF SUB. PUMP SETS FOR 6 " (150 MM) BOREWELLS
SUITABLE FOR 415 V (-10 % TO +6 %), 2880 RPM, 50 HZ., AC POWER SUPPLY

MODEL	HP	STAGE	HEAD IN MTRS	DISCHARGE IN LPM						
				0	535	705	900	1020	1150	1290
NPNN25/2	5.0	2	HEAD IN MTRS	26	22	28	17	12	10	6
NPNN25/3	7.5	3		39	33	37	25	18	15	9
NPNN25/4	10.0	4		52	44	47	43	24	20	12
NPNN25/5	12.5	5		65	55	56	43	30	25	15
NPNN25/6	15.0	6		78	66	75	51	36	30	18
NPNN25/7	17.5	7		91	77	93	60	42	35	21
NPNN25/8	20.0	8		104	88	112	68	48	40	24

NANO T TYPE TABLES

